

Model S2200D

Make-Up Air Heater (Concealed Flame)



*sold
exclusively by*



- Ductable up to 200 feet
- Flame safeguard control provides safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Fused disconnect switch permits easy, safe 100% power shut-off
- Hi limit switch protects heater by shutting down if unit is being overfired
- Motor overload/manual reset protects heater by shutting down if voltage is too low
- Remote thermostat automatically cycles the heater high - low to maintain room temperature

SPECIFICATIONS

Input	2,250,000 BTU/Hr High 1,950,000 BTU/Hr Lo (propane) 1,650,000 BTU/Hr Lo (natural gas)
Fuel	Vapor Propane/Natural Gas
Gas Consumption	24.5 GPH Propane/2250 CFH NG
Electrical	240V 1Ø Amp 30 208-240V 3Ø Amp 20 480V 3Ø Amp 10
Fan	12,000 CFM 5.0 HP, 3.0" S.P.
Thermostat	High/Lo/Off
Temp Rise	350°F
Dimensions	88"L x 46"W x 58"H
Weight	860 lbs.



Gas Supply:	Inlet Pressure		Manifold Pressure
	Max PSI	Min W.C.	W.C.
Propane	5	12"	0.4" - 0.7"
Natural	5	12"	2" - 4.6"

(Minimum inlet pressure is for purpose of input adjustment)



342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com