


heat wagon



342 N. Co. Rd. 400 East
Valparaiso, IN 46383

219-464-8818 • 888-432-8924 • Fax 800-255-7985

Model 4200 Series

SPECIFICATIONS

Input	4210: 5,000,000 BTUH	
	4215: 6,000,000 BTUH	
	4220: 7,000,000 BTUH	
Fuel	Vapor Propane, Natural Gas	
	Liquid Propane (see model chart)	
Inlet Pressure	Max PSI	Min PSI
	250 PSI	30 PSI
Manifold Pressure	15 PSI	
Gas Consumption	4210: 54.6 GPH LP, 5000 CFH NG	
	4215: 65.6 GPH LP, 6000 CFH NG	
	4220: 76.5 GPH LP, 7000 CFH NG	
Gas Connection	1/2" NPT	
Electrical Requirements	4210: 240V 1Ø 60A, 240V 3Ø 40A	
	4215: 240V 3Ø 50A, 480V 3Ø 30A	
	4220: 240V 3Ø 60A, 480V 3Ø 40A	
Fan	4210: 27,500 CFM 10HP	
	4215: 33,500 CFM 15 HP	
	4220: 40,100 CFM 20 HP	
Thermostat	HI-LO	
Dimensions	99"L x 64"W x 78"H	
Weight	4210: 1140 lbs	
	4215: 1250 lbs	
	4220: 1350 lbs	



Propane or Natural Gas
Portable Space Heater

Model Chart

Model	Fuel	Power
4210-1	Natural Gas	1Ø 240V
4210-2	Natural Gas	3Ø 240V
4210-3	Natural Gas	3Ø 480V
4210-4	Liquid Propane	1Ø 240V
4210-5	Liquid Propane	3Ø 240V
4210-6	Liquid Propane	3Ø 480V
4215-1/4220-1	Natural Gas	3Ø 240V
4215-2/4220-2	Natural Gas	3Ø 480V
4215-3/4220-3	Liquid Propane	3Ø 240V
4215-4/4220-4	Liquid Propane	3Ø 480V

Features

- Air flow switch
- Ductable
- Flame safeguard control
- Fused disconnect switch
- Hi limit switch
- Manifold pressure gauge
- Motor overload - manual reset
- Panel mounted voltage meter
- Remote thermostat
- Weather sealed control box

Benefits

- Safe fuel shutdown if combustion air is interrupted
- May be ducted up to 400 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Direct wire with easy, safe 100% power shut off
- Protects heater by shutting down if unit is being overfired
- Helps in diagnosing specific gas flow problems
- Protects heater by shutting down if voltage is too low
- Easy monitoring of control voltage to ensure trouble-free operation
- Automatically cycles the heater on/off
- Indoor/outdoor usage

www.heatwagon.com