

CLEAN DRY HEAT!



Model SVG1500

Indirect Fired Gas Heater

- Versatility of dual fuel - natural gas & propane
- Compact design uses less space both on the job and during off-season storage
- Long life stainless steel heat exchanger
- 3-stage remote thermostat control conserves fuel
- High fuel efficiency
- Large volume blower with 2" static pressure

**NEW
FOR
2006**



Certified

**Set It And
Forget It!**

SPECIFICATIONS

Input	1,500,000/ 1,100,00 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	16.4 GPH Propane/1,500 CFH NG
Gas Connection	1-1/2" FNPT
Electrical	208/230/460 Volts 33/30/15 amp circuit (3ø) 208/230 Volts 56/51 amp circuit (1ø)
Fan	7,272 CFM
Thermostat	3 Stage Hi/Lo/Off
Temp Rise	171°F @ 0°F Ambient
Rated Efficiency	80%
Dimensions	114"L x 32.5"W x 77.5"H
Duct Size	24"x24"
Approx. Weight	1,875 lbs.

Gas Supply:	Inlet Pressure	
	Max PSI	Min W.C.
Propane	5	12"
Natural	5	12"

heat wagon 

342 N. Co. Rd. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com