

CLEAN DRY HEAT!



Model VG175

Indirect Fired Gas Heater

Perfect For Residential
Construction

- 100% clean, dry heat.
- Dual fuel - switch from propane to natural gas in minutes.
- Approved for indoor/outdoor applications.
- Ductable to 25 ft.
- Remote thermostat with 15 ft. cord.
- Compact design fits through standard doorway.
- Whisper quiet blower.



Set It And Forget It!

MEA Pending

SPECIFICATIONS

Input	175,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	1.9 GPH Propane/175 CFH NG
Gas Connection	3/4" FNPT
Electrical	120 Volts 15 amp circuit
Fan	1,400 CFM 1/2" SP
Thermostat	Standard On/Off
Temp Rise	200°F @ 0°F Ambient
Rated Efficiency	80%
Shipping Dim.	43"L x 15"W x 38"H
Duct Size	8" (up to 25' straight)
Approx. Weight	186 lbs.

Gas Supply:	Inlet Pressure	
	Max W.C.	Min W.C.
Propane	14"	9"
Natural	14"	9"



342 N. Co. Rd. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com