The Industry
Workhorse
Trusted For Over
25 Years
Just Got
BETTER!

Model S1505B

Direct Fired Heater

Component upgrades virtually eliminate electrical service calls



- Efficient motor reduces amp draw and is rated to run on standard 15 amp circuit.
- New remote (15' long) thermostat with Hi/Lo/Off control.
- Relays pull in and hold tight down to 50V.
- · Upgraded heater control board . . .
 - starts heater with low voltage down to 95V
 - now with built-in diagnostics
 - runs stable when voltage drops down to 83V
 - potted control board minimizes moisture and vibration
 - rated to -40°F



Set It And Forget It!

SPECIFICATIONS

Input 1,500,000 - 850,000 BTU/Hr
Fuel Vapor Propane/Natural Gas
Gas Consumption 16.4 GPH Propane/1500 CFH NG

Gas Connection 1 1/4" FNPT

Electrical 120 Volts 15 amp circuit

Fan 7000 CFM 1 HP

Thermostat 2 Stage Hi/Lo/Off w/15'Remote

Temp Rise 490°F

Shipping Dim. 69"L x 32"W x 41.5"H

Approx. Weight 300 lbs.

Gas Supply:	Inlet Pressure		Manifold Pressure	
	Max W.C.	Min W.C.	Max W.C.	Min W.C.
Propane	14"	9"	2.7"	0.75"
Natural	14"	9"	7.2"	2.0"

heat wagon

