

CLEAN DRY HEAT!



Indirect Fired Oil Heaters

Oil Fired Heating
Just Got Easier!

- 100% clean, dry heat.
- Approved for indoor/outdoor applications.
- Ductable to 50 ft.(VF400) and 200 ft.(VF1000)
- Remote thermostat with 15' cord.
- Compact design fits through standard doorway.
- Large capacity fuel tanks (optional).
- In-line fuel circulation heater ensures smooth start-up.
(Tested to -20°F)



Model VF400

MEA 29-05-E



Model VF1000



MEA 29-05-E

SPECIFICATIONS

	VF400	VF1000
Input	400,000 BTU/Hr	1,000,000 BTU/Hr
Fuel	#1 or #2, Kerosene, Diesel or Fuel Oil	Fuel Oil
Fuel Consumption	3.0 GPH	7.2 GPH
Electrical	120 Volts 20 amp circuit	240 Volts 1 ϕ 30 amp circuit
Fan	2,100 CFM 1/2" SP	4,075 CFM 2.0" SP
Thermostat	Standard On/Off	Standard On/Off
Temp Rise	200°F @ 0°F Ambient	200°F @ 0°F Ambient
Rated Efficiency	80%	80%
Duct	12" Dia. (up to 50' straight)	20" Dia. (up to 200' straight)
Shipping Dim.	60"L x 24"W x 45"H	120"L x 31.5"W x 54"H
Approx. Weight	400 lbs.	1,300 lbs.



Certified

**Set It And
Forget It!**

heat wagon

342 N. Co. Rd. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com

Accessories




FT400-Fuel Tank

- 75 gallon tank
- Single wall tank
- Forklift capability from all four sides
- Use with VF400 heater
- Minimum 25 hour run time
- 160 lbs. (empty)
- 750 lbs. (full)




FT1000-Fuel Tank

- 225 gallon tank with fuel gauge
- Double wall tank
- Forklift capability from all four sides
- Use with VF1000 heater
- Minimum 30 hour run time
- 1,000 lbs. (empty)
- 2,600 lbs. (full)



Immersion Heater for VF1000 Fuel Tank

- 120V (500 watts)
- Keeps fuel at optimal flow rate
- Overtemp safety circuit



Immersion Heater for VF400 Fuel Tank

- 120V (1000 watts)
- Prevents fuel "gelling"

Circulation Fuel Preheater for VF400

- Ensures quick smooth "cold weather" start-up
- Standard on VF1000



Ducting

Wire Reinforced

- Max. temp. limit 350°F

Poly Duct

- Max. temp. limit 200°F



- Thermostat controlled