

Model IX405

Indirect Fired Gas Heater

SURE FLAME

- Built Sure Flame "Construction Tough" for long life and reliability
- Stackable design for efficient off season storage
- 16" puncture proof wheels for easy maneuverability
- Designed with return air recirculation for increased fuel savings
- 3 year warranty on combustion chamber
- Single stage external thermostat included
- Highest temperature rise and fan rating among other 400K IDF models
- Dual fuel selector valve enables quick change between propane and natural gas
- Operates on 15 amp, 120 V circuit



sold exclusively by

heat wagon

**Your Best Value
In The Market!**

**See Product
Comparison
(on back)**

SPECIFICATIONS

Input	400,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	4.4 GPH Propane/400 CFH NG
Electrical	120 V, 12 Amps
Fan	5000 CFM
Thermostat	On/Off
Temp Rise	250° F @ 0°F Ambient
Rated Efficiency	90%
Dimensions	82" x 29" x 59"
Duct Size	2-12" or 1-16" outlets
Recirculation Inlet	16"
Weight	560 lbs.

heat wagon

342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com

Product Comparison

Manufacturer	Frost Fighter, IDH400QR	Flagro, FV-400RC	Wacker, HI 400HD G	Sure Flame IX 405
BTU input rate	390,000	390,000	381,000(NG), 335,000 (LP)	400,000
Blower fan volume Static pressure	2800 CFM 2.8" WC	4000 CFM	3750 CFM 0.6" WC	5000 CFM 2.65" WC
Duct	2-12" outlets Ductable to 100'	2-12" outlets Ductable to 150'	1-20" outlet Ductable to 60'	2-12" outlets Ductable to 100'
Fan type Fan HP	Centrifugal blower 1.0 HP	Centrifugal blower 1.0 HP	Axial fan 1.0 HP	Centrifugal blower 1.0 HP
Amp draw	20 amp circuit	15 amp circuit	15 amp circuit	12 amps 15 amp circuit
Flue stack included	NO	NO	NO	YES
Thermostat included	NO	NO	NO	YES
CSA certified	YES	NO	YES	YES
Combustion chamber Warranty	ONE YEAR	ONE YEAR	ONE YEAR	THREE YEARS
Recirculation capability	YES	YES	YES	YES
Temperature rise	190 F at 0 degrees	150 F at 0 degrees	126 F at 0 degrees	250 F at 0 degrees
Weight	420 lbs	470 lbs	434 lbs	560 lbs
Foot print	70" x 32"	70" x 29" (14 sq ft)	81" x 34" (19.1 sq ft)	82" x 29" (16.5 sq ft) stackable design

*Information above was obtained from manufacturers website for each product listed.