

SURE FLOME

SOLD EXCLUSIVELY BY

IX800

DUAL FUEL/INDIRECT 800,000 BTU

X800 800,000 BTU / Hr



Features: 🍩 🏵



- · Quick change fuel supply.
- Patented Sure Flame engineered burner & exchanger.
- Easy access to burner and electrical controls.
- Fork lift and pallet jack pockets.
- Single point lifting hook.
- Accepts both 1-phase and 3-phase electrical input as standard feature.
- Single switch control for convenient simple operation.
- VFD "Soft Start" control provides smooth startup with lower amp draw.
- Remote thermostat / standard equipment.
- Recirculation feature.
- 3 Year Warranty *

Specifications .

Heat Input Heater Efficiency	Approx. Fuel Consumption			Fan Rating	Heat Rise Motor Power		er	Dimensions (LxWxH)	
800,000 BTU / Hr 86%	33 L / Hr 36.9 Lbs	/ Hr (propane) 800 Cl	FH (natural gas)	13,600 CFM*	72°C	208/230 V - 1	Ph or 3 Ph	95" x 29" x 58"	
Max Amp Load 208/230V - 1 Ph	208/230V - 3 Ph	Inlet Diameter	Outlet Diamet	er Max Duct	Length I	Flue Diameter	Weight	Gas Connection	Gas Supply Pressure
43.2 / 39.1 A	27.7 / 25.1 A	20"	2x 16" / 1x 20"	200'		10"	1340 Lb	1" NPT	1/2 to 5 PSI

*Advertised CFM is the fan rating, not the output CFM. Actual CFM output will vary depending on operating conditions.

See sureflame.ca/warranty for coverage.