



heat wagon

Model VG750
Model VG1100

Indirect Fired Gas Heaters



- Versatility of dual fuel - natural gas & propane
- Reliable Riello burner
- Remote thermostat
- Wheels for easy portability
- Long lasting stainless steel combustion chamber
- High static centrifugal blower
- Ductable to 150 ft.
- Recirculation capability
- Very low noise fan ≤ 69 dB
- Includes flue stack

SPECIFICATIONS

	VG750	VG1100
	750,000 BTU/hr	1,000,000 BTU/hr
Fuel	Vapor Propane/Natural Gas	Vapor Propane/Natural Gas
Gas Consumption	8.3 GPH Propane/750 CFH NG	11 GPH Propane/1000 CFH NG
Burner	Riello N750S	Riello N900S
Gas Connection	1.25" FNPT	1.25" FNPT
Electrical	240 Volts 20 Amps	240 Volts 25 Amps
Fan	9400 CFM, 1.2" Static Pressure, 3HP	11,200 CFM, 1.2" Static Pressure, 4HP
Thermostat	Remote On/Off with 50' cord	Remote On/Off with 50' cord
Temperature Rise	110°F	110°F
Dimensions	100"L x 36"W x 64"H	104"L x 41"W x 73"H
Duct Outlet (max duct length)	1-30" Dia. (150'), 2-20" Dia. (90')	1-30" Dia. (150'), 2-24" Dia. (90')
Duct Inlet (recirculation)	30" Dia., 30' Max Length	30" Dia., 30' Max Length
Approx. Weight	948 lbs.	1,160 lbs.

heat wagon 

342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com