

Model 4200

Direct Fired Heater



- May be ducted up to 400 feet
- Safe monitoring of combustion, two trial electronic ignition with 20 second pre-purge time delay and 7 second shutdown
- Fused disconnect switch permits easy, safe 100% power shut-off
- Hi limit switch protects heater by shutting down if unit is being overfired
- Motor overload/manual reset protects heater by shutting down if voltage is too low
- Panel mounted voltage meter
- Remote thermostat automatically cycles the heater high - low to maintain room temperature

sold exclusively by



SPECIFICATIONS

Input	4210 - 5,000,000 BTU/Hr 4215 - 6,000,000 BTU/Hr 4220 - 7,000,000 BTU/Hr
Fuel	Vapor & Liquid Propane/Natural Gas
Gas Consumption	4210 - 54.6 GPH Propane/5000 CFH NG 4215 - 65.6 GPH Propane/6000 CFH NG 4220 - 76.5 GPH Propane/7000 CFH NG
Gas Connection	3/4" FNPT - NG/Vapor Propane 1/2" FNPT - Liquid Propane
Electrical	4210 - 208-240V 1Ø 60 Amp, 208-240V 3Ø 40 Amp 4215 - 208-240V 3Ø 50 Amp, 480V 3Ø 30 Amp 4220 - 208-240V 3Ø 60 Amp, 480V 3Ø 40 Amp
Fan	4210 - 27,500 CFM, 10 HP 4215 - 33,500 CFM, 15 HP 4220 - 40,000 CFM, 20 HP
Duct (optional)	46" Diameter
Thermostat	High - Low
Temp Rise	200°F
Dimensions	139"L x 72"W x 78"H
Weight	4210 - 1,200 lbs. 4215 - 1,210 lbs. 4220 - 1,420 lbs.

MODEL CHART

Model	Fuel	Power
4210-1	Natural Gas	1Ø 240V
4210-2	Natural Gas	3Ø 240V
4210-3	Natural Gas	3Ø 480V
4210-4	Liquid Propane	1Ø 240V
4210-5	Liquid Propane	3Ø 240V
4210-6	Liquid Propane	3Ø 480V
4215-1/4220-1	Natural Gas	3Ø 240V
4215-2/4220-2	Natural Gas	3Ø 480V
4215-3/4220-3	Liquid Propane	3Ø 240V
4215-4/4220-4	Liquid Propane	3Ø 480V

Gas Supply:	Inlet Pressure		Manifold Pressure
	Max PSI	Min PSI	PSI
Vapor Propane	250	20	15
Natural	250	20	15

For lower pressures consult Heat Wagon Tech Service



342 N. 400 E. Valparaiso, IN 46383
219-464-8818 • 219-462-7985 • www.heatwagon.com