


Model 950H

Direct Fired Heater

Component upgrades virtually eliminate electrical troubleshooting

- Dual-fuel quick change over from propane to natural gas
- Can be utilized as make-up air heater
- Efficient motor reduces amp draw and is rated to run on standard 15 amp circuit
- New remote (50' long) thermostat with Hi/Lo/Off control
- 12" wheels make for easy handling
- Relays pull in and hold tight down to 95V
- Ductable up to 100 ft.
- Upgraded heater control board . . .
 - starts heater with low voltage down to 95V
 - potted control board minimizes moisture and vibration
- Diagnostic troubleshooting lights



- Can run fan only as an industrial blower

SPECIFICATIONS	
Input	950,000 - 650,000 BTU/Hr
Fuel	Vapor Propane/Natural Gas
Gas Consumption	10.4 GPH Propane/950 CFH NG
Gas Connection	1-1/4" FNPT
Electrical	120 Volts 15 amp circuit
Fan	7000 CFM, 1-1/2 HP, 1" W.C. SP
Duct (optional)	WD2425HT
Thermostat	2 Stage Hi/Lo/Off w/50'Remote
Temp Rise	250°F
Actual Dimensions	39"H x 73"L x 30.5"W
Weight	360 lbs.



Model 950HL available as liquid withdrawal unit.



Gas Supply:	Inlet Pressure	
	Min PSI	Max PSI
Propane	1	20
Natural	3	20

(Minimum inlet pressure is for purpose of input adjustment)

