

Model S1505B

Direct Fired Heater

Component upgrades virtually eliminate electrical troubleshooting

- CSA Certified
- Efficient motor reduces amp draw (9.4 amp) and is rated to run on standard 15 amp circuit
- Remote (15' long) thermostat with Hi/Lo/Off control
- Relays pull in and hold tight down to 50V
- Upgraded heater control board . . .
 - starts heater with low voltage down to 95V
 - built-in diagnostics
 - runs stable when voltage drops down to 83V
 - potted control board minimizes moisture and vibration
 - rated to -40°F
- Quick changeover from propane to nautral gas with a turn of a ball valve
- Tough sturdy frame allows easy stacking and saves storage space
- · Lifting loop and carry bars makes moving simple

SPECIFICATIONS

heat wagon

Input	1,500,000 - 850,000 BTU/Hr		
Fuel	Vapor Propane/Natural Gas		
Gas Consumption	16.4 GPH Propane/1500 CFH NG		
Gas Connection	1 1/4" FNPT		
Electrical	120 Volts 15 amp circuit		
Fan	7000 CFM 1 HP		
Thermostat	2 Stage Hi/Lo/Off w/15'Remote		
Temp Rise	490°F		
Shipping Dim.	69"L x 32"W x 41.5"H		
Approx. Weight	300 lbs.		

Gas Supply:	Inlet Pr	Inlet Pressure		
	Max W.C.	Min W.C.		
Propane	14"	9"		
Natural	14"	9"		
(Minimum inlet pressure is for purpose of input adjustment)				

sold

exclusively by

SCAN ME

342 N. 400 E. Valparaiso, IN 46<mark>383</mark> 219-464-8818 • 219-462-7985 • www.heatwagon.com

Rev. 6-22



Compare For YOURSELF!

S1505B

	•	
TH	EI	RS

Temp. Rise	490°F	454°F
CSA Certified	Yes	No
Thermostat	2 stage hi/low/off	Hi/low only;
	Remote w/15' of cable	mounted on control box
Electrical Rating	9.4 amps	13.6 amps
Fan Delay Timer	10 sec.	No delay, the fan
		runs continuously
Required Electrical	15 amps	20 amps
Service		
Heater Control	Can start up with	Shuts down heater
	voltages as low as 95V	with voltage drop
	and run stable at 83V	to 104V
Polarity Sensitive	No	Yes
Metal Finish	Durable powder coating	Standard paint

Call For Your Complete Heat Wagon Product Guide!



342 N. 400 E. Valparaiso, IN 46383 219-464-8818 • 219-462-7985 • www.heatwagon.com