Model S405

Direct Fired Heater

- CSA certified for unattended operation
- Stainless steel burner and heat shield
- Dual Fuel Quick changeover from propane to natural gas with turn of ball valve
- Air flow switch and Hi limit switch ensures safe operation
- Thermostat to conserve fuel
- Thicker gauge steel construction and powder coated finish ensures durability

| SPEC | IFICATIONS |
|-----------------|----------------------------|
| Input | 400,000 BTU/Hr |
| Fuel | Vapor Propane/Natural Gas |
| Gas Consumption | 4.4 GPH Propane/400 CFH NG |
| Gas Connection | 1" FNPT |
| Electrical | 115 Volts 12 amp circuit |
| Fan | 2000 CFM 1/4 HP |
| Thermostat | On/Off |
| Temp Rise | 344°F |
| Shipping Dim. | 46"L x 18"W x 24"H |
| Min Temp | -40°F |
| Shipping Weight | 100 lbs. |
| | |





| Gas Supply: | Inlet Pr | essure | |
|-------------------------|----------|--------|--|
| Gas Supply: Max W.C. | Min W.C. | | |
| Propane | 14" | 7" | |
| Natural | 14" | 7" | |

Recommend 40SV06 regulator





219-464-8818 • 219-462-7985 • www.heatwagon.com

Shown with optional wheel kit ACC-SWK1

sold exclusively by

SURE FLAME



Rev. 6-22